

# AbsorbaSound™ PLUS

AbsorbaSound PLUS  
For use as underlayment for Laminate and floating wood floor installation

- *Pre-Consumer recycled rubber*
- *LEED benefits*
- *IIC 60, STC 54*
- *Lifetime Warranty*
- *Residential & Commercial applications*
- *Superior Sound Deadening*
- *Water Resistant*
- *Fire Retardant, Code Compliant*
- *Mold & mildew resistant*
- *Lays flat, easy to install*



## PRODUCT SPECIFICATIONS

### **MATERIAL:**

Contains 96% pre-consumer rubber being recycled to protect the environment, minimize landfills, while making LEED contribution. Colors will vary. Other thicknesses available.

### **THICKNESS & MASS:**

2.0MM. 68 Lbs/Cubic Foot. Very dense and supportive

### **SOUND:**

*AbsorbaSound* has been professionally tested using the American Society for Testing and material Protocol ASTM E492-04, and classified in accordance with STM E989-89 earning a classification of 60 IIC, 54 STC. It is further stated that comparing equal thicknesses and equal test methods for other underlays, *AbsorbaSound* will provide superior results of sound attenuation and support.

### **MOISTURE:**

Rubber is waterproof. *AbsorbaSound* is designed for utmost sound deadening and support. If any floor is being installed on or below grade, professional results dictate that a continuous moisture barrier of 6 Mil plastic inset over the floor and extending 1" up the walls under the baseboard (NO SEAMS) be used.

### **FLAMMABILITY:**

Tested as a rubber floor according to BS EN ISO 9239-1: 2002. Used as an underlay, covered by laminate or floating wood flooring. *AbsorbaSound* meets or exceeds all requirements of fire code.

### **FUNGUS/MILDEW:**

*AbsorbaSound* is non-absorbent so will not support mold and mildew. No harsh chemical treatments are necessary. Flooding will not harm the underlay.

### **WEIGHT:**

43 Lbs. - 4'x25' = 100 s/f roll size.