

QUIETWALK®

PREMIUM ACOUSTIC UNDERLAYMENT

Delta Δ IIC 24
 IIC 71 | IIC 60
assembly | NO ceiling assembly
 STC 66 | STC 54
NO ceiling assembly

For Use Under

- Laminate Flooring
- Hardwood Flooring

Installation Methods

- Floating Floors



EXCELLENT
SOUND
ABSORPTION



EXCLUSIVE
MOISTURE
PROTECTION



SMOOTHING
FLOOR
IMPERFECTIONS



APPROVED
FOR INFLOOR
HEATING



ADDING
INSULATION
VALUE



CLEAN
INDOOR AIR
QUALITY



94%
RECYCLED
MATERIALS



INSTALLATION METHODS

FLOATING FLOORS

1. Roll out underlayment vapor barrier side up and butt seams together. Perimeter edges need to be 1/2" to 3/4" from the wall.
2. Seal seams with provided lip and tape (when included), or similar moisture resistant, utility-grade seam tape with aggressive adhesive (duct tape).
3. Click & lock floating floors over the top according to manufacturer.

*ENSURE TO READ THE COMPLETE INSTALLATION INSTRUCTIONS BEFORE INSTALLATION

ENVIRONMENTAL ATTRIBUTES

- QuietWalk is GREENGUARD and GREENGUARD Gold certified for low chemical emissions (UL2818) and conforms to Collaborative for High Performance Schools (CHPS) – CA Section 01350
- QuietWalk contains 94% post industrial/pre-consumer fibers.
- QuietWalk is LEED™ compliant and will contribute to:
 - MRc4.1-4.2 recycled content credit
 - EQ 4.3 low-emitting materials credit

LIMITATIONS

QuietWalk is not suitable for use as underlayment for:

- Ceramic tile
- Glued-down wood
- Sheet-vinyl
- VCT
- Installations over concrete in high moisture areas (vapor emission rate above 5lbs/1000 sq ft/ 24 hrs as measured with a calcium chloride test kit) will require additional protection such as a concrete sealant or polyethylene vapor barrier.

APPROVED SUBSTRATES

- Dry, completely cured concrete (at least 28 days old)
- Concrete and masonry blocks
- Cement backer units (CBU)
- Cementitious screeds, leveling coats and mortar beds
- Waterproofing and crack-isolation membranes
- Wood, plywood, or OSB subfloors that meet NWFA Subfloor Guidelines and Specifications, and meet applicable building codes
- Cement terrazzo floors

PACKAGING

3' x 33.4' (100 sq ft) do-it-yourself size rolls
 Rolls per pallet: 30 Weight per pallet: 400lbs
 Pallets per truck: 64 Rolls per truck: 1920
 6' x 60' (360 sq ft) contractor sized rolls available

Moisture Absorption Properties

Moisture Absorption Approx. 650% by weight

Moisture Statement. QuietWalk will absorb and allow dispersion throughout the product of water moisture in accumulations not exceeding one gallon per 24 hrs per 300 square feet of product and/or allowed to continue to accumulate for more than 7 days. Actual in-house tests have shown results up to 5 times that amount.

QW100B1LT

RATED RESIDENTIAL AND COMMERCIAL

TECHNICAL DATA

Physical Properties: Blended synthetic fibers and polyethylene film. Inert hot-melt adhesive.

Antimicrobial Protection Yes
 Weight 12 lbs/roll • 17.28 oz/sq yd • 1.92 oz/sq ft
 Thickness 0.125"
 Density 11.52 lbs / ft³
 Compression Resistance @ 25% 9.5 psi
 Compression Resistance @ 30% 16.6 psi
 Compression Resistance @ 50% 85.5 psi
 Breaking Strength Length 72.1 lbs; Width 100 lbs
 Compression Set @ 25% 18.8%
 R-Value (@0.125") 0.58 hr-ft²-degF/Btu (4.64/ inch)

Flammability Meets or exceeds Federal Flammability Standard: 1-70 (Pill Test) and ASTM E84 Steiner Tunnel Test.

Volatile Organic Compounds (VOC) Tested for 81 different off-gas compounds in accordance with CA 01350. Passed to the level of Collaborative for High Performance Schools (CHPS) and Office Spaces.

Product Emissions Passed the most rigorous emissions test: Section 01350 for CHPS and Standard Office 8mm Laminate.

SOUND PROPERTIES

IMPACT SOUND TRANSMISSION

The method is designed to measure the impact sound transmission performance of a floor-ceiling assembly in a controlled laboratory environment.

IIC	Flooring	Sub-floor
71	Laminate	WITH ceiling assembly
57	Floating Engineered Wood	WITH ceiling assembly
68	Laminate	WITH/suspended gypsum board assembly
60 (Field IIC)	Laminate	NO ceiling assembly
55	Laminate	6" concrete slab with no ceiling assembly
59	Engineered Wood	Fire Rated System - UL L521 Wood frame with 3/4" gypsum concrete
61	Floating Engineered Hardwood	Wood frame, gypsum concrete, isolation clips
59	Floating Engineered Hardwood	Wood frame and gypsum concrete

SOUND TRANSMISSION LOSS

The sound-insulating property of a partition element is expressed in terms of the sound transmission loss.

STC	Flooring	Sub-floor
66	Floating Engineered Wood	WITH suspended gypsum board assembly
54	Laminate	NO ceiling assembly
52	Laminate	Wood frame and gypsum concrete
50	Laminate	6" concrete slab with no ceiling assembly
61	Engineered Wood	Fire Rated System - UL L521 Wood frame with 3/4" gypsum concrete
59	Floating Engineered Hardwood	Wood frame, gypsum concrete, isolation clips
61	Floating Engineered Hardwood	Wood frame and gypsum concrete

DELTA TEST

Tests the impact insulation difference between a bare concrete subfloor with no flooring materials and the same concrete subfloor with flooring and underlayment.

Delta IIC	Flooring
24	QuietWalk under Laminate



SCAN the code for testing & downloadable reports

