

DuoFoam™

ECONOMY GRADE with SELF SEAL



For Use Under:

- Laminate and Engineered Wood
- Floating Engineered Wood

ADVANTAGES



MOISTURE RESISTANT

Polyethylene Foam with special moisture resistant film on both sides.



LIP AND TAPE STRIP

Patented Absolute™ Lip & Tape strip for additional moisture protection and ease of installation



ECONOMICAL

Quality flooring underlayment that won't break the bank.

INSTALLATION STEPS

1. Read flooring manufacturers recommendations and instructions.
2. Be sure to sweep, vacuum and remove debris on the substructure.
3. Fill in any significant holes, gaps or breaks in the substructure.
4. Roll out underlayment over the substructure surface. To connect rolls using the self-seal tape, simply join the extended lip to the end of the next roll by peeling off the liner of the adhesive tape and adhering it to the extended film lip.
5. Always be sure to connect the rolls together evenly so that the foam is not overlapping each other and no gaps exist.



PRODUCT SPECIFICATIONS

Thickness:

.080 (before film lamination)

Film Thickness:

1 mil HD/LD in and out
(includes self sealing tape and adhesive)

WVTR (Water Vapor Transmission rate):

6.95 g/m²/24 hour day, (.45 g/100in²/24 hour day)

Standard roll sizes:

40" x 30.03' (100 sf) - 48 rolls per box
40" x 300.30' (1000sf) - 5 rolls per box

Stock Colors:

White foam and clear film

PACKAGING

Insulayment is available in

40" x 30' (100 sq. ft.)
1.016 m x 9.14 m (9.2 m²)

do-it-yourself size rolls.

*Always read manufacturer's instructions before installing DuoFoam underlayment.

