

TruFüze ARMOR

For use under Floating Engineered Wood and Laminate Floors

Sound Specifications
Industry's Top Delta Rating

Delta Δ IIC 24

IIC 68
6" concrete WITH
ceiling assembly

STC 63
6" concrete NO
ceiling assembly



**Sound
Control**



**Moisture
Protection**



**Heat Reflective
Lining**



**Recycled
Materials**

- Can use over concrete and wood subfloors
- Excellent sound control, helps to stop noise from traveling
- Exceeds industry requirements for moisture protection
- Superior compression characteristics to support click-together system
- Suitable for radiant heated floors
- Film lip and self-sealing tape for ease of installation
- Mold and mildew resistant
- Made from recycled foam materials

Sound control and moisture protecting underlayment

INSTALLATION INSTRUCTIONS

FLOATING FLOOR:

1. Be sure the Subfloor surface is clean and dry
2. Unroll the underlayment over the subfloor with the silver film barrier side up
3. Extend the underlayment all the way to the wall, leaving no gaps or overlap
4. Seams need to be butted together flush, do not overlap the pad.
Peel back the adhesive liner on the tape and adhere to the film lip.
5. Install laminate flooring according to the manufacturer's installation instructions.



48" x 25' (100 sf roll)

MPglobal
www.mpglobalproducts.com

MADE IN CANADA

